



OPERATING INSTRUCTIONS SHARK TRAILERS

BEFORE OPERATING:

- Read operators manual carefully prior to using
- Check engine oil and fuel levels
- Secure high-pressure hose to machine
- Connect to garden hose (minimum 5/8" @ 20 psi)
- Fill storage tank as required with water if running from storage tank
- Wear protective clothing

STARTING OPERATION USING WATER FROM A GARDEN HOSE:

- Put desired spray nozzle into quick connect collar on tip of spray wand
- Turn on water at faucet (fully)
- Turn lever below plaque to the vertical position
- Turn lever opposite the operators station to the vertical position
- With the spray nozzle pointing away from you or anybody else, press the trigger on the spray gun to relieve pressure
- Start engine
- Trigger spray gun to obtain pressurized water spraying out of spray nozzle
- Press rocker switch on burner control panel to the ON position
- Burner will now light automatically
- Shortly, the water spraying from the nozzle will become HOT

TO START OPERATING USING WATER FROM THE STORAGE TANK:

- Fill the storage tank with water
- Turn lever on the valve below the plaque to the horizontal position to draw water from the storage tank
- With the spray nozzle pointing away from you or anybody else, press the trigger on the spray gun to relieve pressure
- Turn lever on opposite side of control station to the horizontal position
- Start engine
- Trigger spray gun to begin cleaning
- Press burner rocker switch on control panel to the ON position
- Burner will light automatically
- Shortly, the water spraying from the nozzle will become HOT

TO SHUT DOWN:

- Shut burner off first by pressing the burner rocker switch on control panel to the OFF position
- Continue spraying until water from the nozzle is allowed to cool below 100 degrees
- Stop engine